

Rust Lock

PRODUCT DATA



Description

Rust Lock is a high-performance water based low odour and environmentally friendly primer treatment, this product neutralises rust and forms a tough black surface that's suitable for over-coating with solvent based primers or top coats.

Area of use

Interior and Exterior

Substrates

Ferrous Metals

Packing

1 litre, 2.5 litres and 5 litres (min batch 200L)

Physical Constants

Colour:	Black, Grey, Sage Green
Finish:	Satin
Volume solids:	42%
Theoretical spreading rate:	2-3 sq. metres per 250 ml
Flash point:	N/A
Specific gravity:	1.20
Dry to touch:	30 mins
Over-coating time:	4-6 hours

****The theoretical spreading rate** has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants** are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, Spray*
Thinner:	*Minimum DFT 75µm, adjust accordingly for rough surfaces.
Cleaning of tools:	Water

Surface Condition

Ensure surface is free from all flaking material, dust, dirt, oil and grease. Metals (especially new/forged items) may require degreasing. Do not apply in temperatures below 10 degree centigrade.

*Please refer to the Material Safety Data Sheet for further information.
Please check colour before use. If using multiple cans please check batch numbers are the same.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.